

## VUKA DEEP CLEAN DC

### DESCRIPTION

Vuka Deep Clean is a caustic base heavy duty alkaline cleaner for grease, oil, fat and blood. Applications including smokehouses, dairies, cheese factories, breweries, meat plants, fryer and most demanding industrial applications.

### DILUTION

Cleaning level required and dosage.

Heavy	5%	1L in 20L water
Very Heavy	10%	2L in 20L water

### MIXING

Add the required dosage to water and stir with a flat paddle for 1 minute.

### APPLICATION

Pour gently over the floor area, use squeegees or hard bristle brooms to spread. Allow contact time of 5 to 10 minutes for solution to stand over floor area for best results. Scrub floors with mechanical scrubbers. Squeegee off and dispose of waste water in a suitable manor. Apply only clean water and scrub again, repeat this step. Flush with clean water. Repeat entire cycle if required. Apply a water break free test to determine if all residual chemical has been properly rinsed away.

### SUITABILITY WITH EQUIPMENT

Before using in cleaning machinery contact the manufacturer to ensure compatibility.

### CAUTION

Corrosion risk with non ferrous metals due to high alkalinity.

### STORAGE

24 Months from date of production if stored in original sealed containers in dry conditions at temperatures between +5 C and +30 C.

Email: [info@vukafloors.co.za](mailto:info@vukafloors.co.za)

Revision date: June 2016

### HEALTH AND SAFETY

Use of basic principles of industrial hygiene and protective clothing such as gloves, goggles, masks will enable the product to be used safely. Splashes into eyes should be washed immediately with clear water for 5 minutes and medical advice sought.

### FURTHER INFORMATION

Vuka Floors products are guaranteed against defective materials and manufacture and are sold subject to its Terms and Conditions which may not be overridden in any other legal documentation.

Whilst any information contained herein is true, accurate and represents our best knowledge and experience at the date of issuance it is subject to change without prior notice. User must contact Vuka Floors to verify correctness before specifying or ordering. No warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

Figures given for consumption / spread rates are theoretical and do not allow for additional materials due to surface profile, porosity, variations in level and wastage etc.